

cio

Perfection
has its
price.



ZIVELO™

C10 Specifications

Body	<p>Material: 5052 Aluminum Thickness: 10 Gauge / 0.100" / 2.5mm Welding: Tig with Anodizable Rod Cut Type: Laser and CNC Turret Bend Radius: 0.41" / 1.03mm Finishing: Electrostatic Powder Coating, Class A Finish</p>
Poles	<p>Material: 6063 T6 Aluminum Thickness: 8 Gauge / 0.125" / 3.2mm Welding: Tig with Anodizable Rod Cut Type: CNC Machined Curve Radius: 0.63R Finishing: Electrostatic Powder Coating, Class A Finish</p>
Display	<p>Type: LCD Size: 42" Diagonal Aspect Ratio: 16:9 Resolution: 1920 X 1080 (1080p) Brightness: 500cd/m2 (nit) Contrast: 5000:1 Response Time: 5ms Viewing Angle: 178 Horizontal and Vertical Color Support: 24 Bit (16.7M Colors) Signal Input: VGA, RF, HDMI (x4), RCA Audio (x2), RCA Video (x2), SVideo Signal Output: RCA Audio, SPDIF Digital Optical Audio, Headphones Dot Pitch: 0.485mm Power: 100-240VAC</p>
Sound	<p>System: Logitech™ Surround Speaker System, 1 Subwoofer, & 2 Satellites Features: Integrated Power & Volume Control in Control Base Power: 17 Watts RMS Power (34 Watts Peak) Satellite Power: 8 Watts (16 Watts Peak) Subwoofer Power: 9 Watts (18 Watts Peak) Freq. Response: 50Hz - 20kHz Power Cable Length: 5 feet / 1.5 meters Headphone Jack: 3.5mm Microphone Jack: 3.5mm</p>
Access	<p>Lock: PIN Code Enabled Electronic Lock with Keypad Door: Security Door Made of Aluminum With Security Lip on all Sides Door Hardware: Quick Release Spring Latches Locking Mechanism: Dual Rotary Latch with Steel Cam and Linkages</p>
Cooling	<p>Fan Type: Tube Axial Fan Bearings: Sealed Case: Aluminum Filter: Metal Mesh Filter (Replaceable) CFM: 37 Voltage: 115VAC RPM: 2700 dBA: 33 Vent Holes: Multiple in Cabinet</p>
Power	<p>Type: Ultra Compact UPS System Power: 180 Watts Storage: 350VA Outlets: 6 Powered / 3 Protected Surge: Yes, Protection Other: Audible Alarm, Replaceable Battery</p>
Packaging	<p>Style: Corrugated Box with Dual Tray System Material: Kraft Paper Rating: 250# Cushion: 1.75 Poly Ethylene Foam</p>
Environmental	<p>Operating Temp: 30F - 90F (-1C - 32C) Storage Temp: 10F - 110F (-12C - 43C) Humidity Range: 10-80%</p>
Compliances	ISO-9001, FCC, UL, CE, ADA, RoHS
Warranty	<p>Cabinet: 5 Years Limited Electronics: 1 Year Limited Extension: Options Available</p>

C10 Dimensions

