

C6

The C6 Thin Floor
Standing Public
Terminal allows for
an inviting user
experience with
its solid aircraft
aluminum body and
minimalistic
European design.



Copyright 2009 ZiveLo Corp ZC609R1.2.17

ZIVELO™

C6 Specifications

Body	<p>Material: 5052 Aluminum Thickness: 10 Gauge / 0.100" / 2.5mm Welding: Tig with Anodizable Rod Cut Type: Laser and CNC Turret Bend Radius: 0.14" / 3.5mm Finishing: Electrostatic Powder Coating, Class A Finish</p>
Poles	<p>Material: 6063 T6 Aluminum Thickness: 8 Gauge / 0.125" / 3.2mm Welding: Tig with Anodizable Rod Cut Type: CNC Machined Curve Radius: 0.63R Finishing: Electrostatic Powder Coating, Class A Finish</p>
Display	<p>Type: LCD Size: 19" Diagonal Aspect Ratio: 4:3 Resolution: 1280 X 1024 (75Hz) Brightness: 300cd/m2 (nit) Contrast: 800:1 Response Time: <5ms Viewing Angle: 160 Horizontal and Vertical Color Support: 24 Bit (16.7M Colors) Max Sync Rate: 76Hz X 81kHz Signal Input: VGA Dot Pitch: 0.294mm Power: 120/230VAC</p>
Sound	<p>System: Logitech Dual Satellite Speaker System Features: Integrated Power and Volume Control Power: 2.3 Watts RMS Power (4.6 Watts Peak) Freq. Response: 50Hz - 20kHz Power Cable Length: 5 feet / 1.5 meters Headphone Jack: 3.5mm</p>
Access	<p>Lock: PIN Code Enabled Electronic Lock with Keypad Door: Security Door Made of Aluminum With Security Lip on all Sides Door Hardware: Quick Release Spring Latches Locking Mechanism: Dual Rotary Latch with Steel Cam and Linkages</p>
Cooling	<p>Fan Type: Tube Axial Fan Bearings: Sealed Case: Aluminum Filter: Metal Mesh Filter (Replaceable) CFM: 37 Voltage: 115VAC RPM: 2700 dBA: 33 Vent Holes: Multiple in Cabinet</p>
Power	<p>Type: Safety Power Strip Voltage: 120V AC Frequency: 60Hz Output Amps: 15 Outlet Type: NEMA 5-15R Outlet Number: 6</p>
Packaging	<p>Style: Corrugated Box with Dual Tray System Material: Kraft Paper Rating: 250# Cushion: 1.75 Poly Ethylene Foam</p>
Environmental	<p>Operating Temp: 30F - 90F (-1C - 32C) Storage Temp: 10F - 110F (-12C - 43C) Humidity Range: 10-80%</p>
Compliances	ISO-9001, FCC, UL, CE, ADA, RoHS
Warranty	<p>Cabinet: 5 Years Limited Electronics: 1 Year Limited Extension: Options Available</p>

C6 Dimensions

